



HIGH CLOGGING/PIPING POTENTIAL FINE GRAINED SOILS DETAIL

NOT TO SCALE

NOTES:

1. OVERLAP MIRAFI FW402 PER INSTALLATION GUIDELINES (MIN 12-INCHES).
2. MIRAFI FW402 ACTS AS A PERMEABLE SEPARATOR BETWEEN SAND AND DRAIN ROCK.
3. SAND LAYER STOPS INTRUSION/PIPING OF FINE GRAINED SILT/CLAY SOIL THROUGH MIRAFI FW402.


TENCATE
GEOSYNTHETICS
365 SOUTH HOLLAND DRIVE
 PENDERGRASS, GEORGIA 30567
 TEL: (706) 693-2226
 WWW.TENCATEGEO.US

NOTE: THE STANDARD DETAILS ILLUSTRATED IN THESE DRAWINGS ARE FOR INFORMATION AND EVALUATION PURPOSES ONLY AND ARE NOT FOR CONSTRUCTION. PROJECT SPECIFIC CALCULATIONS, SHOP DRAWINGS AND SPECIFICATIONS, SIGNED AND SEALED BY A REGISTERED LICENSED ENGINEER, ARE REQUIRED FOR CONSTRUCTION.

FRENCH DRAIN WITH HIGH FINES

STANDARD DETAIL
NOT FOR CONSTRUCTION

DATE : 6/5/20

EXHIBIT

A-1